

UCHIDA BUSINESS CARD CUTTER

BC-10 (New Layout Version)

For improving the usability, BC-10 features additional layout patterns of business cards. The main features of this new layout are...

1. Increasing the variety of cutting mode (European version)

New BC-10 has 5 cutting mode in one version (old version can be selected 2 or 3 cutting mode from one version).

2. Special cutting mode (US version)

In US version, BC-10 additionally featured new two special cutting modes. One is for cutting 4 tickets with perforation line from one sheet of letter size paper with using the optional perforator unit. The other one is for making 12 pcs of business cards from one sheet of Legal size paper.

3. Countermeasure against static electricity

As the remedy for influence of static on the paper, BC-10 additionally feature a new cutting mode to cut the 8 business card from 1 sheet.



Specifications

| Machine version | European Version I | European Version II | US Version |
|---|---|---|---|
| Cutting Mode | 55 x 85mm (S-10) 55 x 85mm (D-10) 55 x 85mm (D-8) 51 x 85mm (D-10) 50 x 85mm (D-10) | 55 x 90mm (S-10) 55 x 90mm (D-10) 55 x 90mm (D-8) 51 x 90mm (D-10) 50 x 90mm (D-10) | 2.0" x 3.5" (S-10) 2.0" x 3.5" (D-10) 2.0" x 3.5" (D-8) 2" 3/8 x 7" 1/2 (Ticket) 2.0" x 3.5" (Legal D-12) |
| Paper Thickness | 110~300g/m2 (0.15 to 0.30mm)* 1 | | |
| Cutting Speed | 10 sheets/min. | | |
| Stacking capacity of Paper Feed tray | 50 sheets (In case of sheet thickness of 0.2mm) | | |
| Counter | Addition or preset subtraction is selective | | |
| Dimensions | 585(W) x 428(D) x 325(H) mm (23.0" x 16.9" x 12.8") | | |
| Net weight | 21.0Kg (46.3 lbs) | | |
| Voltage | 220-240V AC 50/60Hz or 100-120V AC 50/60Hz | | |
| Power consumptions | 32W/0.44Amp (220-240V machine), 27W/0.4Amp (100-120V machine) | | |
| Error detection | Paper jam, cut mark detection error, no slitter unit, top cover opened and no waste box | | |
| Optional Unit | Slitter unit, perforation unit, scoring unit | | |
| Safety standards | CE (European version) or UL (US version) | | |
| Cutting accuracy | ±0.1 mm (Single cut), ±0.18 mm (Double cut) in paper feed direction | | |

* 1: Applicable paper thickness is effective for short grained paper only.

• Specifications are subject to change without notice.


UCHIDA YOKO CO., LTD.

• Refer to new layout patterns on back side.


Layout of bussiness cards

European Version I


**Cutting mode #1
Single cut**




**Cutting mode #2
Double cut**




**Cutting mode #3
Double cut**



**Cutting mode #4
Double cut**




**Cutting mode #5
Double cut**




European Version II


**Cutting mode #1
Single cut**




**Cutting mode #2
Double cut**




**Cutting mode #3
Double cut**



**Cutting mode #4
Double cut**




**Cutting mode #5
Double cut**




US Version


**Cutting mode #1
Single cut**




**Cutting mode #2
Double cut**




**Cutting mode #3
Double cut**



**Cutting mode #4
Double cut**



**Cutting mode #5
Double cut**



UCHIDA YOKO CO., LTD.

9-15, Shiomi 2-chome, Koto-ku, Tokyo, JAPAN
 TEL:+81-3-5634-6350
 FAX:+81-3-5634-6856 & 5634-6857
 URL:<http://www.uchida.co.jp/global/>
 E-mail:overseas@uchida.co.jp